

DATA CENTER | ELITE SERIES

CONTAINMENT PANELS

Keep IT Contained with Elite Containment Panels

Missing cabinets, uneven aisle ends, and cityscape cabinet heights presents a challenge to many containment designs. Subzero Engineering Wall Panels easily fill in all sizes of gaps to create one continuous containment solution. Elite Series Panel Frames are 1.5" x 1.5" (38.1 mm x 38.1 mm).



subzeroeng.com

CONTAINMENT PANELS

Product Specifications

		Property	Material	Result	
	Frame	Physical Properties			
		Tensile Strength	Aluminum	22,000 psi	
	Shipping	Physical Properties			
		Weight		15-17 lbs. (6.80kg - 7.71kg)	
		Components		1 Major Component	
	Panel Inserts	3mm — Acrylic Flammability			
	(Optional)	Smoke Dev.	ASTM E84	Class A	
		Flame Speed	ASTM E84	Class C	
		Horizontal Burn	ASTM D635	1.18 in/min (29.97 mm)	
		UL Horizontal	UL94	94 HB	
Key Features		4mm — Twin Wall Polycarbonate Flammability			
		Smoke Dev.	ASTM E84	Class A	
Custom Sizes		Flame Spread	ASTM E84	Class A	
Rigid Design		6mm — Twin Wall Polycarbonate Flammability			
		Smoke Dev.	ASTM E84	Class A	
Clear Panels		Flame Spread	ASTM E84	Class A	
 Modular Design 		3mm — FM4910 Flammability			
		-	UL94	VO	
Product Options		_	FM4910	Yes	

Clear or Black Finish

Over Rack or Floor Mounted

> order height Panel Insert 1.5" (38.1 mm) → panel width

Drawings

